

# 제품 사양

## TECHNICAL SPECIFICATIONS

### CLASSIFICATION

Type of floor covering	Heterogenous Resilient Floorcovering	EN 1401:2004
Classification	23 31	EN 429

### DIMENSIONS

Width x Length	169 X 1210 mm	ISO 24342
Total thickness	5 mm	ISO 24346
Wear layer thickness	0.50 mm	ISO 24340
Nos. of planks per box	10 pcs	
Square meter per box	2.04 sqm	
Square feet per box	21.96 sqft	
Weight per box	18 kg	
Surface treatment	Reinforced micro-ceramic treatment with UV protection	
Click system	Angle click & lock licensed by Valinge	
Edges	4 sides micro bevelled edges	

### GENERAL DATA

Curling after heat	< 0.4%	ISO 23999
Dimension stability	< 0.25%	ISO 23999
Flexibility	No crack found	ISO 24344
Residual indentation	< 0.1mm Pass	ISO 24343
Castor chair test	Pass	ISO 4918 (EN425)
Fire classification	Bf1 - s1	EN ISO 9239-1
Abrasion resistance	Wear group T	EN 660-2
Slip resistance	Class DS	EN 13893
Chemical resistance	High resistance	ASTM F925-02(08)
Thermal conductivity	Pass	EN 12667-2001
Colour fastness to light	>Garde 6	ISO 10582:2010
Impact sound transmission	Pass	ASTM E492-09

### ENVIRONMENT & CERTIFICATES

Emission of Formaldehyde	Not detected	ISO 16000-3/6/9
Contents of Pentachlorophenol PHP	Not detected	BS 5666 PART 6
TVOC	Pass	EN 16516-2017
Phthalate Test	Not detected	ISO 17353-2004
Prohibited Heavy Metals	Not detected	ASTM F963-17